



# P26 Multi-Purpose MoS<sub>2</sub> Lubricant

## Dewatering & Penetrating Fluid

Issue: January 2016

PRODUCT CODE	PACK SIZE	CTN / QTY
P26MPL0004	400 ml	6



### Product Description

**P26 Multi-Purpose MoS<sub>2</sub> Lubricant** is an advanced formula, professional and universal automotive maintenance oil, containing molybdenum disulphide, that infiltrates, penetrates, dispels water, lubricates moving parts, acts as a contact agent (electrical), cures squeaks & creaks and protects metal against corrosion. It contains a solvent carrier that evaporates from the treated components whilst leaving a thin film of corrosion protecting oil.

### Application

**P26 Multi-Purpose MoS<sub>2</sub> Lubricant** is suitable for use in all automotive, marine, industrial & domestic applications. These include drying wet automotive ignition and electrical systems and is useful in many other automotive and domestic applications such as hinges, locks, catches and other squeaking or seized moving parts. It can also be used as a corrosion protector for metal.

**P26 Multi-Purpose MoS<sub>2</sub> Lubricant** can be used wherever a normal penetrant or light lubrication is necessary to assist in free movement of parts. It is excellent as a penetrant pre-spray for rusted on nuts and bolts prior to disassembling corroded parts.

**P26 Multi-Purpose MoS<sub>2</sub> Lubricant** can help eliminate problems by protecting exposed parts from corrosive effects of climatic conditions especially in high humidity and areas close to coastal sea & salt. It acts as a water dispelling or displacement fluid so is excellent for contact points.

**P26 Multi-Purpose MoS<sub>2</sub> Lubricant** is flammable and should be kept away from flames and ignition sources. It has a non-toxic formulation and does not stain metal surfaces.

### Instructions for use

- 1) Use directly from the aerosol spray can
- 2) Spray on to problem area
- 3) Leave product for a few minutes to penetrate

### Product Benefits

- Protects against corrosion, rust and oxidation
- Acts as a water displacement fluid
- Many & varied product uses
- Stops squeaks & creaks
- New design spray nozzle with built in tube

### Typical Data

Colour

Brown-Grey liquid

Density at 15°C, kg/L

0.83

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

# PENRITE



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 748)  
 Fax: 1800-PENRITE (1800 736 748)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**

