



# PAS FLUID

## Power Steering & Suspension Fluid

Issue: May 2016

Product Code	Pack Size	Carton Qty
PAS001	1 Litre	6



### Description

Penrite PAS Fluid is a premium, semi synthetic oil specially designed for use in Australian, European, US & Korean power steering and suspension systems. Contains a special **Anti-Shudder** (noise & chatter) additive.

PAS Fluid fully meets the requirements of Land Rover PAS 14315.

### Application

PAS Fluid is recommended for use in the power steering and active cornering control system (ACE) of Land Rover vehicles such as the Discovery and Defender.

PAS Fluid also meets or exceeds the requirements for power steering units used by Chrysler and General Motors North America and for ZF power steering units. It may be used in power steering units where automatic transmission fluids are specified and use of a semi-synthetic fluid is desired

PAS Fluid can be used where products such as Pentosin CHF 7.1 or 4548 are recommended and where Dexron VI is recommended in Holden Commodore / Calais / Caprice & HSV VE series vehicles.

PAS Fluid can also be used where 7.5W motorcycle fork oil is required.

PAS Fluid Other applications include the power steering and suspension systems of:

Aston Martin	BMW	Dodge	Ferrari	Ford
Holden / HSV	Hyundai	Infiniti	Jaguar	Jeep
Kia	Mazda	Mercedes Benz	Nissan	SAAB
Subaru	Volvo			

Penrite also market Power Steering Fluid, LHM Plus, MB 15, and LDAS special power steering and suspension fluids. Please check your handbook or call Penrite to clarify any applications for these products.

### Product Benefits

- Semi synthetic performance
- Minimises shudder & noise.
- Extends seal and hose life.
- Good low temperature fluidity.
- Protects against rust and corrosion.

### Industry Standards

Land Rover STC 50717 (ACE)	ZF TE ML-09/B	GM 9985835, 9985819	Chrysler MS-5931
Chrysler MS-9462	MB 236.3	MB 341	PAS 14315
Esso EZL 998 (Jaguar S)	Opel 90 513486	Ford M2C128-C/D	AM4124
VW TL-VW-570-26	Ford M2C195-A (Power steering only)		

### Typical Data

Colour	Green
Density at 15°C, kg/L	0.86
Viscosity, Kinematic, cSt	
at 40°C	25.6
at 100°C	6.4
Viscosity Index	196
Phosphorus, mass %	0.021
Viscosity, Brookfield, cP at -40°C	4,500

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

# PENRITE



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 748)  
 Fax: 1800-PENRITE (1800 736 748)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**

