Power Steering Fluid

Premium Mineral Fluid

Issue: June 2015

Product Code	Pack Size	Carton Qty
PSF0005	500ml	6
PSF001	1 Litre	6
PSF020	20 Litre	1

Description

Power Steering Fluid is a premium mineral based, multipurpose power steering fluid designed for use in power steering units that specify a conventional type **Automatic Transmission Fluids** (ATF's) ie Dexron II & III Fluids. It contains special **anti-shudder** additives not found in ATF's that are designed to provide enhanced wear protection, longer service life and reduce noise in all conditions.

Power Steering Fluid meets the requirements of Ford M2C134-C/D.

Application

Power Steering Fluid is designed for use in **Australian, US, Japanese, European & Korean** manufactured power steering units in cars and trucks that originally use an automatic transmission fluid such as:

Alfa Romeo	Daewoo	Diahatsu	Daimler	Mitsubishi	Kia
Eunos	Ford	Holden	Hyundai	Jaguar	Maserati
Lamborghini	Lancia	Lexus	Lotus	MG	Renault
Mazda	Nissan	Peugeot	Porsche	Proton	Volvo
Rover	Subaru	Suzuki	Toyota	Triumph	*and many others*

Power Steering Fluid is also suitable for all Ford EF-FG, Territory SX-SY Series, Tickford & FPV series vehicles where **Ford M2C134-C/D** is specified.

Power Steering Fluid **should not** be used in Honda units (use **Penrite HPSO**), electronic power steering systems or in systems that use highly specialised or synthetic fluids such as **Penrite LHM Plus**, **LDAS, HDPS,** or **PAS** fluids. It is not recommended for Land Rover Ace systems or in European vehicles that require CHF 11S fluids or where Dexron VI is specified by the manufacturer (use **Penrite PAS** Fluid).

Product Benefits

- Minimises shudder (noise & chatter) in power steering pumps
- Effective anti wear additives provide wear protection
- Protects against rust and corrosion
- Long service through good thermal stability

Industry Specifications

Ford M2C134-C/D* PS 11872 GM 9985010 Chrysler MS-1872

** not for use in tractors*

Typical Data

Colour	Amber
Density at 15°C, kg/L	0.880
Viscosity, Kinematic, cSt	
at 40°C	66
at 100°C	10.8
Viscosity Index	157
Zinc, mass %	0.139

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926

United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com