PRO 10

Semi Synthetic 10W-30 Engine Oil

Issue: March 2015

Product Code	Pack Size	Ctn / Qty
PRO10020	20 Litre	1
PRO10060	60 Litre	1
PRO10205	205 Litre	1

Description

Pro 10 is a premium grade, semi synthetic SAE 10W-30 engine oil developed for use in modern petrol engines exclusively in professional workshops and vehicle service centres. It uses a combination of the latest additive technology and a low shear rate viscosity modifier, to ensure additional protection against wear, corrosion, oil oxidation, piston deposits and sludge under tough conditions.

Pro 10 exceeds API **SN** Resource Conserving and ILSAC GF-5 fuel economy specifications as well as many manufacturers' requirements.

Application

Pro 10 is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines.

Pro 10 is recommended where the manufacturer specifies a SAE 7.5W-30 or 10W-30 engine oil.

Pro 10 is ideal for –

Ford AU/BF/FG series	Ford Territory SX/SY/SZ (Petrol)	Holden VY/VZ/VE series
Honda Accord / Civic / City / CRV	Toyota Camry / Aurion / Corolla	Toyota Camry Hybrid
Mitsubishi ASX (Petrol)	Mitsubishi Lancer & Outlander	Mazda 3 & 6 series
Nissan Dualis / Micra / Tida		

As well as many others manufacturers and models

Pro 10 is suitable for use with Petrol, E10 and E85. As an ILSAC GF-5 rated product, it is highly suited for use in vehicles that can run on ethanol based fuels such as E85. It is also suitable for use in petrol/electric hybrid powered vehicles such as Toyota, Lexus & Honda.

Note: Pro 10 is **NOT** designed for use in diesel engines or in Mazda Rotary Engines.

Product Benefits

- **LATEST** oil specification technology exceeding **API SN**
- Fuel efficient **ILSAC GF-5** product
- Suitable for use with E85 Fuel
- Suitable for use in Hybrid petrol/electric vehicles
- Minimises sludge formation
- Maximises wear protection
- Reduces piston deposits

Industry Specifications

API SN Resource Conserving | ILSAC GF-5 | Ford M2C 910A

Typical Data

SAE Grade	10W-30
Density at 15°C, kg/L	0.866
Viscosity, Kinematic, cSt	
at 40°C	60
at 100°C	9.8
Viscosity Index	148
Viscosity, Cold Cranking @ -25 °C	3,966
Viscosity, Cold Cranking @ -30 °C	
Zinc, mass %	0.082
Sulphated Ash, mass %	0.95
Base Number	8.3

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926