



PENRITE

PRO EXTRA

Semi Synthetic 10W-40 Engine Oil

Issue: November 2016

Product Code	Pack Size	Ctn / Qty
PROEXTRA020	20 Litre	1
PROEXTRA060	60 Litre	1
PROEXTRA205	205 Litre	1
PROEXTRA1000LTR	1000 Litre	1

Description

Pro Extra is a premium grade, semi synthetic SAE 10W-40 engine oil developed for use in modern petrol, LPG and light duty diesel (Non DPF) engines exclusively in professional workshops and vehicle service centres. It uses a combination of the latest additive technology and a low shear rate viscosity modifier, to ensure additional protection against wear, corrosion, oil oxidation, piston deposits and sludge under tough conditions.

Pro Extra exceeds the latest European ACEA A3/B4 and API SN/CF requirements, as well as many manufacturers' specifications.

Application

Pro Extra is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines.

Pro Extra is recommended where the manufacturer specifies a SAE 10W-30 or 10W-40 grade engine oil and can be used where ACEA A3/B4 is recommended. It can also be used where previous API specifications SM (2004-10), SL (2001-04), & SJ are recommended and suitable for use with LPG and some diesel engine passenger cars, 4WDs and light commercials. It is not suitable for use in diesel vehicles fitted with a diesel particulate filter that require a low "SAPS" engine oil.

Product Benefits

- **LATEST** oil specification technology exceeding **API SN** and **ACEA A3/B4**
- **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- Reduces oil consumption and maintains oil pressure
- Catalytic converter compatible.
- Ideal for light duty diesel engines
- Minimises sludge formation
- Maximises wear protection
- Reduces piston deposits

Industry Specifications

API SN/CF	ACEA A3/B4	VW 501 01	VW 502 00 / 505 00
Renault RN 0700	MB 229.1		

Typical Data

SAE Grade	10W-40
Density at 15°C, kg/L	0.868
Viscosity, Kinematic, cSt	
at 40°C	98
at 100°C	14.1
Viscosity Index	148
Viscosity, Cold Cranking @ -25 °C	5,906
CA content, mass %	0.331
Zinc, mass %	0.109
Sulphated Ash, mass %	1.29
Phosphorus, mass%	1.000
Base Number	10.10

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com