



Product Information

PRO HYDRAULIC OIL

Ashless, premium quality hydraulic oils made from selected base stocks and an advanced anti-wear additive.

APPLICATION

Penrite Pro Hydraulic Oils are recommended for use in all types of hydraulic systems using vane, piston or gear pumps, airline lubricators, vacuum pumps, lightly loaded gear sets and bearings (such as headstocks, windmill gears) and hydraulic hoists and jacks. It may also be used in some types of reciprocating and piston compressors where this type of oil is called for.

CUSTOMER BENEFITS

- Formulated to combat rust, oxidation, wear and foaming.
- Reduces sludge formation.
- Compatible with silver components.
- Provides good water separation.

INDUSTRY SPECIFICATIONS

Denison HF0, HF1, HF2
Vickers I-286-S, M-2950-S
Cincinnati Milacron P-68, P-69, P-70 (HM)
DIN 51524 Part 2 (HLP Type)
US Steel 136, 127

Typical Properties

ISO Grade	32	46	68
Viscosity, Kinematic, cSt			
at 40°C	30.2	44.6	72.1
at 100°C	5.1	6.7	9.0
Viscosity Index	94	103	98

Penrite Oil Company Pty Ltd
ABN 25 005 001 525
Ph: 1300 PENRITE (1300 736 748)
Int: 61 3 980 1 0877
Email: penrite@penriteoil.com
www.penriteoil.com.au

ENVIRONMENT, HEALTH AND SAFETY

Information is available by request on this product in the Penrite Material Safety Data Sheet. Information in this sheet is based on the most current information available. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacture.

Issued September 2005