



Product Information

RAPID 7 FLUSH

Penrite Rapid 7 Flush is a fast acting, alkaline cleaner which removes rust, scale and other deposits from automotive cooling systems.

APPLICATION

Recommended for use to clean out the radiator cooling system of all types of vehicles/engines before any of the Penrite branded inhibitor or anti-freeze products are introduced into an automotive cooling system.

INSTRUCTION FOR USE

- 1 Drain cooling system by opening heater valve and disconnecting bottom radiator hose and drain open tap.
- 2 Reconnect hose and close tap
- 3 Fill cooling system with fresh water while adding one bottle of Rapid 7 Flush.
- 4 Run engine to normal operating temperature so that thermostat opens. Run for 7 minutes and repeat drain procedure. Do not leave

product in system for any longer than 2 hours maximum.

- 5 Check all gaskets, hoses and seals. Check all hose to engine connections and remove any deposit build up.
- 6 Attach all fittings, ensuring a secure sealed fit.
- 7 Add required amount of Penrite cooling system product according to directions on bottle.

**CAUTION – HIGHLY ALKALINE: KEEP OUT OF REACH OF CHILDREN
AVOID CONTACT WITH SKIN, EYES AND CLOTHING.**

CUSTOMER BENEFITS

- Compatible with all types of coolants including new organic products.
- Fast acting

Typical Properties

Density at 15°C	1.08
Colour	Blue
pH	12.2

Penrite Oil Company Pty Ltd
ABN 25 005 001 525
Ph: 1300 PENRITE (1300 736 748)
Int: 61 3 980 1 0877
Email: penrite@penriteoil.com
www.penriteoil.com.au

ENVIRONMENT, HEALTH AND SAFETY

Information is available by request on this product in the Penrite Material Safety Data Sheet. Information in this sheet is based on the most current information available. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacture.

Issued September 2005