



Product Information

RUBBER GREASE

A premium quality clay based grease containing castor oil for use when contact with natural and/or synthetic rubber is likely to occur.

APPLICATION

Penrite Rubber Grease can be used as a general purpose, non-harmful grease for industrial, automotive and consumer rubber parts such as hydraulic dust covers, braking system components, seals and washers. It is specially designed for use on rubber components in hydraulic systems where compatibility with the rubber seals is essential. It is also suitable for use with other rubber components such as gaiters or boots used on these systems

This grease is also recommended in other applications where the resistance to hydrocarbon solvents is required, such as automotive shock absorbers. In the assembly of platen rollers used in the printing industry this type of grease is used as a lubricant to aid the insertion of the steel mandrel into the very tight rubber outer.

Recommended operating range is -9°C to 80°C.

Penrite Rubber Grease is **not** recommended for the lubrication and protection of brake backing plates and plunger housings.

CUSTOMER BENEFITS

- Excellent lubricity
- Compatible with natural and synthetic rubbers
- Easy to use
- Long storage life
- Protects against rust and corrosion
- Resists hydrocarbon solvents (such as petrol)

INDUSTRY SPECIFICATIONS

NLGI 2

Typical Properties

| | |
|-------------------------|-----|
| NLGI | 2 |
| Base Oil Viscosity, ISO | 320 |
| Drop Point, °C | 275 |
| Colour | Red |

Penrite Oil Company Pty Ltd
ABN 25 005 001 525
Ph: 1300 PENRITE (1300 736 748)
Int: 61 3 980 1 0877
Email: penrite@penriteoil.com
www.penriteoil.com.au

ENVIRONMENT, HEALTH AND SAFETY

Information is available by request on this product in the Penrite Material Safety Data Sheet. Information in this sheet is based on the most current information available. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacture.
Issued April 2007