



SHELSLEY ENGINE OILS

Codes: *SHELL005, SHELM005, SHELM020, SHELH005*

Issue: August 2012

A range of very low detergent engine oils designed specifically for petrol and diesel fuelled vintage, pre-war and post-war vehicles to 1950.

Application

SHELSLEY LIGHT

Small capacity vintage engines relying totally on splash lubrication. Also suitable for small capacity sleeve valve engined cars such as Minerva, Mors, Knight and Daimler. Can be used for vehicles operating where cooler ambient temperatures will be experienced.

Ideal for use in early vintage (pre 1950) motorcycles, incorporating sight glasses, pilgrim oil pumps and total loss lubrication systems.

SHELSLEY MEDIUM

Larger engined vintage and pre-war vehicles which have either troughs or dipper type lubricating systems, or early types of pressure fed systems. Also suitable for those employing total loss oiling systems and for larger capacity sleeve valve engined cars such as Minerva, Mors, Knight and Daimler. Can be used for vehicles operating where moderate ambient temperatures will be experienced.

SHELSLEY HEAVY

Recommended for use in large engined vehicles operating in high ambient temperatures, or in vehicles with oil consumption problems. Ideal in large capacity sleeve valve engines fitted to such makes as Minerva, Mors, Knight and Daimler.

Customer Benefits

- Extends bearing and gear life by minimising wear and shock loads
- Minimises sludge build up, bearing corrosion and piston ring sticking through the use of selected additive technology.
- Reduces foaming by using an effective anti-foam agent
- Optimised zinc levels for wear protection
- Formulated to give much improved low temperature pumpability and flow than old style SAE 30 (Light), 40 (Medium) or 50 (Heavy) oils while improving operating temperature wear protection.

Industry Specifications

API SC/CC

Typical Data

	LIGHT	MEDIUM	HEAVY
Density at 15°C, kg/L	0.884	0.884	0.884
Flash Point, °C	214	221	212
Viscosity, Kinematic, cSt			
at 40°C	216	286	286
at 100°C	23.8	28.5	29.7
Viscosity Index	137	140	140
Magnesium, mass %	0.125	0.125	0.125
Zinc, mass %	0.140	0.140	0.140
Phosphorus, mass %	0.128	0.128	0.128



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

PENRITE