



# HI-PER TWO STROKE ENGINE OIL

## Semi Synthetic 2 Stroke Oil

Issue: April 2017

PRODUCT CODE	PACK SIZE	CTN QTY
SEHPTS001	1 Litre	6
SEHPTS0025	2.5 Litre	4
SEHPTS020	20 Litre	1
SEHPTS205	205 Litre	1



### Description

**Hi-Per Two Stroke Engine Oil** is a high performance, semi synthetic, low smoke, low ash two stroke engine oil made from the latest synthetic additives and premium base oils. It exceeds many manufacturer requirements including API TC, JASO FC & ISO EG-C requirements.

### Application

**Hi-Per Two Stroke Engine Oil** is suitable for use in all types of two stroke engines including motorcycles, mopeds and scooters that use either a premix or oil injection system. It is suitable for use in two stroke chainsaws, brush cutters, lawn mowers and other gardening equipment in domestic and industrial use. It is also suitable for stationary engines and industrial power units.

**Hi-Per Two Stroke Engine Oil** is suitable for use and exceeds the requirements for Sea-Doo Personal Water Craft (PWC)

### Product Benefits

- Low smoke, Low Ash formulation
- Extends engine life
- Good anti-scuff properties
- Maximises spark plug life
- Reduces exhaust port blockages
- Keeps piston rings free from deposits
- Mixes readily with petrol
- Enhanced lubricity and detergency, keeping engines clean

### Industry Specifications

API TC

JASO FC

ISO EG-C

### Typical Data

Colour	Red/Orange
Density at 15°C, kg/L	0.862
Viscosity, Kinematic, cSt	
at 40°C	57
at 100°C	9.0
Sulphated Ash, mass %	0.09
Base Number	1.6

### 2 Stroke Mixing Chart

Fuel / Oil Ratio	ml per 1 Litre of fuel	ml per 5 Litres of fuel	ml per 10 Litres of fuel	<b>For Example:</b> If your machine requires a 25:1 fuel to oil ratio and you have a 5 Litre fuel container, you would add 200 ml of Two Stroke oil to your fuel container prior to re-fuelling.
16:1	63	313	625	
20:1	50	250	500	
25:1	40	200	400	
50:1	20	100	200	

Note: Refer to Operators Handbook for correct Fuel to Oil ratio.

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

# PENRITE



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 748)  
 Fax: 1800-PENRITE (1800 736 748)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**

