



Product Information

SMALL ENGINE

FOUR STROKE MONOGRADE 30

Penrite Small Engine Four Stroke Oil SAE 30 is a non-friction modified engine oil formulated from modern additives to ensure protection against wear, corrosion, oil oxidation and sludge.

APPLICATIONS

Penrite Small Engine Four Stroke Oil SAE 30 is designed for use in small engines in lawnmowers, generator sets and pumps, four stroke outboards, four stroke brushcutters and in other gardening implements such as those in the following chart.

Ariens
Briggs and Stratton (side valve)
BSA
Clinton
John Deere
Kawasaki

Simpson
Robin
Suffolk
Tecumseh
Toro
Villiers

Kohler*
Pope

Wisconsin
Onan

* some models require SAE 10W-30. See Small Engine Multigrade Info sheet.

CUSTOMER BENEFITS

- Provide for excellent engine cleanliness and wear protection.
- Protect against rust and corrosion.

INDUSTRY SPECIFICATIONS

Penrite Small Engine Four Stroke Oil 30 meets the performance requirements of:

API SG/CC

MIL-L-2104B

Typical Properties

Density at 15°C, kg/L	0.888
Flash Point, °C	231
Viscosity, Kinematic, cSt	
at 40°C	90
at 100°C	11.3
Viscosity Index	113
Sulphated Ash, mass %	0.79
Zinc, mass %	0.158
Phosphorus, mass %	0.144
Colour	Red

Penrite Oil Company Pty Ltd
ABN 25 005 001 525
Ph: 1300 PENRITE (1300 736 748)
Int: 61 3 980 1 0877
Email: penrite@penriteoil.com
www.penriteoil.com.au

Environment, Health and Safety

Information is available by request on this product in the Penrite Material Safety Data Sheet. Information in this sheet is based on the most current information available. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacture.

Issued July 2008