



## Product Information

# STORAGE OIL SUPPLEMENT

Penrite Storage Oil Supplement is a combination of an effective synthetic corrosion inhibitor and carrier oil.

### APPLICATION

It is designed to increase the anti-corrosion performance of standard lubricants both in service or when equipment is stored for long periods of time.

For Automotive use:

500ml will treat up to 10L. For extended storage in humid environments, it may be used at up to 10 times that level. It may be used in engines, gearboxes, transmissions and differentials.

For Industrial use:

Use at 5% in gear boxes and hydraulic systems that will be stored for extended periods of time or up to 15% in extremely humid or salty conditions. A treat rate of 2% will provide boosted anti corrosion protection and improve oil demulsibility in equipment that is in continual use.

### BENEFITS

- Excellent corrosion control even in humid and/or salty environments
- Gives corrosion protection equivalent to many of the old barium based products
- Increases demusibility for better water separation

### Typical Properties

<b>Colour</b>	<b>Amber</b>
<b>Viscosity</b>	<b>ISO 100</b>
<b>ASTM D665 B Rust Test at 2</b>	<b>Pass</b>

Penrite Oil Company Pty Ltd  
ABN 25 005 001 525  
Ph: 1300 PENRITE (1300 736 748)  
Int: 61 3 980 1 0877  
Email: [penrite@penriteoil.com](mailto:penrite@penriteoil.com)  
[www.penriteoil.com.au](http://www.penriteoil.com.au)

**Environment, Health and Safety**  
Information is available by request on this product in the Penrite Material Safety Data Sheet. Information in this sheet is based on the most current information available. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacture.  
**Issued May 2006**