



## Product Information

# TRANSOIL 90, 140, 250

THREE STRAIGHT GEAR OILS SUITABLE FOR USE IN VETERAN, EDWARDIAN AND VINTAGE GEARBOXES AND SELECTED SPUR AND BEVEL TYPE REAR AXLES.

### APPLICATION

#### TRANSOIL 90

USED PRIMARILY AS A GEARBOX OIL IN MEDIUM TO LARGE VETERAN AND EDWARDIAN CARS. ALSO USED IN GEARBOX APPLICATIONS IN VINTAGE AND PRE WAR CARS. MAY ALSO BE USED AS A REAR AXLE OIL IN MANY LIGHT CARS OR VOITURETTES. DOES NOT CONTAIN ANY AGGRESSIVE LOAD CARRYING ADDITIVES.

#### TRANSOIL 140

IDEAL AS A REAR AXLE OIL IN MOST EDWARDIAN, VINTAGE AND PRE WAR VEHICLES. WHILE IT CAN ALSO BE USED AS A GEARBOX OIL, IT MAY BE TOO HEAVY IN SOME APPLICATIONS. DOES NOT CONTAIN ANY AGGRESSIVE LOAD CARRYING ADDITIVES

#### TRANSOIL 250

A GEAR OIL SUITABLE FOR USE IN REAR AXLES OF VETERAN CARS OF ONE, TWO AND FOUR CYLINDERS. IT CONTAINS A SPECIAL ADDITIVE TO HELP THE LOAD CARRYING ABILITY OF THE OIL. CONTACT WITH ANY WATER OR MOISTURE SHOULD BE AVOIDED OR SEAL DEGRADATION MAY OCCUR. WHILE THIS OIL HAS THE CHARACTERISTICS OF THE OLD 600W OR STEAM CYLINDER OILS, IT SHOULD NOT BE USED AS A STEAM CYLINDER OIL.

NOT TO BE USED IN AXLES FITTED WITH HYPOID GEARS

### *BENEFITS*

- DOES NOT CORRODE FERROUS AND NON-FERROUS MATERIALS.
- COMPATIBLE WITH LEATHER AND SYNTHETIC RUBBER SEALS.

### Typical Properties

	90	140	250
VISCOSITY, KINEMATIC, CST			
AT 40°C	217	480	1200
AT 100°C	20.5	32.4	55

Penrite Oil Company Pty Ltd  
ABN 25 005 001 525  
Ph: 1300 PENRITE (1300 736 748)  
Int: 61 3 980 1 0877  
Email: penrite@penriteoil.com  
[www.penriteoil.com.au](http://www.penriteoil.com.au)

#### Environment, Health and Safety

Information is available by request on this product in the Penrite Material Safety Data Sheet. Information in this sheet is based on the most current information available. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacture.

Issued October 2007