



UPPER CYLINDER AND LPG LUBRICANT

Premium Mineral Oil

Issue: April 2014



Product Code	Pack Size	Ctn / Qty
UCL001	1 Litre	6

Description

Upper Cylinder and LPG Lubricant is a special low viscosity mineral based oil for protection against valve seat recession wear and lubrication of the fuel system in all vehicles. It contains both detergent and lead replacement additives for use in vehicles using leaded, unleaded, E10, LPG or dual fuel.

Application

Upper Cylinder and LPG Lubricant is designed for use in vehicles using leaded or unleaded petrol. It is added directly to the petrol tank at a rate of 50 ml of **Upper Cylinder and LPG Lubricant** per 50 litres of petrol. Graduations on the pack help to ensure correct dosage rates. Always add Penrite Upper Cylinder Lubricant to the tank before adding fuel. A dosage of 100ml per 50L will assist in keeping the fuel system clean for better engine performance.

Upper Cylinder and LPG Lubricant is also designed for use in vehicles using LPG as the only or primary fuel. Penrite Upper Cylinder and LPG Lubricant may be added through dripper systems at a rate of 4-5 drops per minute.

Upper Cylinder and LPG Lubricant is safe for use in vehicles fitted with catalytic converters and oxygen sensors.

Please Note: If valve seat protection in vehicles designed to run on leaded petrol is required, then **Penrite Valveshield** should be used.

Product Benefits

When used in petrol or LPG fuelled engines will:

- Keep clean fuel tanks, lines, carburettors and injectors and retain their cleanliness.
- Protect against rust, corrosion and wear in fuel distribution systems;
- Reduce intake valve deposits.
- Improve driveability and assist in improving fuel consumption as a result of the above.

In addition to these benefits, in an LPG fuelled vehicle, Penrite Upper Cylinder Lubricant will:

- Protect against valve seat recession wear.
- Provide a lubricant into the fuel system which is absent with the very "dry" LPG.

Typical Data

Density at 15°C	0.868
Manganese, mass %	0.108
Flash Point, °C	79

Please Note: This product will darken if exposed to light.

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com